

DX³ AC MCBs

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

MCBs for AC applications till 63A

10 kA ISI marked as per IS/IEC 60898-1 2002
Integrated label holder
Sliding bottom clamp
Efficient air channels
Color coded On/Off indication on dolly
Biconnect lower terminals
IP 20 protected terminals
Sliding shutters
Compatible with signal and control Auxiliaries

DC-80 V per pole - 1 kA

C Curve

Single pole 240/410V

4085 80	0.5	1	640	1/10/120
4085 81	1	1	640	1/10/120
4085 83	2	1	634	1/10/120
4085 84	3	1	634	1/10/120
4085 85	4	1	634	1/10/120
4085 87	6	1	390	1/10/120
4085 90	10	1	390	1/10/120
4085 92	16	1	390	1/10/120
4085 93	20	1	390	1/10/120
4085 94	25	1	390	1/10/120
4085 95	32	1	390	1/10/120
4085 96	40	1	892	1/10/120
4085 97	50	1	892	1/10/120
4085 98	63	1	892	1/10/120



4085 90

Single pole + neutral 240V

4086 02	0.5	2	1674	1/5/60
4086 03	1	2	1674	1/5/60
4086 05	2	2	1674	1/5/60
4086 06	3	2	1674	1/5/60
4086 07	4	2	1674	1/5/60
4086 09	6	2	1184	1/5/60
4086 12	10	2	1184	1/5/60
4086 14	16	2	1184	1/5/60
4086 15	20	2	1184	1/5/60
4086 16	25	2	1184	1/5/60
4086 17	32	2	1184	1/5/60
4086 18	40	2	1916	1/5/60
4086 19	50	2	1916	1/5/60
4086 20	63	2	1916	1/5/60



4086 14

* MRP - Maximum Retail Price Inclusive of all taxes including GST.

DX³ AC MCBs

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

Double pole 415V

4086 21	0.5	2	1738	1/40
4086 22	1	2	1738	1/40
4086 24	2	2	1738	1/40
4086 25	3	2	1738	1/40
4086 26	4	2	1738	1/40
4086 28	6	2	1280	1/40
4086 31	10	2	1280	1/40
4086 33	16	2	1280	1/40
4086 34	20	2	1280	1/40
4086 35	25	2	1280	1/40
4086 36	32	2	1280	1/40
4086 37	40	2	2014	1/40
4086 38	50	2	2014	1/40
4086 39	63	2	2014	1/40



4086 37

Triple pole 415V

4086 43	0.5	3	2560	1/32
4086 44	1	3	2560	1/32
4086 46	2	3	2560	1/32
4086 47	3	3	2560	1/32
4086 48	4	3	2560	1/32
4086 50	6	3	2076	1/32
4086 53	10	3	2076	1/32
4086 55	16	3	2076	1/32
4086 56	20	3	2076	1/32
4086 57	25	3	2076	1/32
4086 58	32	3	2076	1/32
4086 59	40	3	3150	1/32
4086 60	50	3	3150	1/32
4086 61	63	3	3150	1/32



4086 55

Triple pole + neutral 415V

4086 65	0.5	4	3248	1/32
4086 66	1	4	3248	1/32
4086 68	2	4	3248	1/32
4086 69	3	4	3248	1/32
4086 70	4	4	3248	1/32
4086 72	6	4	2706	1/32
4086 75	10	4	2706	1/32
4086 77	16	4	2706	1/32
4086 78	20	4	2706	1/32
4086 79	25	4	2706	1/32
4086 80	32	4	2706	1/32
4086 81	40	4	3870	1/32
4086 82	50	4	3870	1/32
4086 83	63	4	3870	1/32



4086 77

Bold Cat.Nos are products normally available with Legrand (India) Stockists.
Cat.Nos that are not bold - delivery within 4 - 8 weeks from the date of order.
Bold packing quantity is our mandatory packing. Orders to be placed by Legrand (India) Stockist in multiples of the same.

DX³ AC MCBs



4086 94

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

Four pole 415V

4086 84	0.5	4	3206	1/32
4086 85	1	4	3206	1/32
4086 87	2	4	3206	1/32
4086 88	3	4	3206	1/32
4086 89	4	4	3206	1/32
4086 91	6	4	2820	1/32
4086 94	10	4	2820	1/32
4086 96	16	4	2820	1/32
4086 97	20	4	2820	1/32
4086 98	25	4	2820	1/32
4086 99	32	4	2820	1/32
4087 00	40	4	4012	1/32
4087 01	50	4	4012	1/32
4087 02	63	4	4012	1/32

D Curve

Single pole 240/415V

4087 06	0.5	1	644	1/10/120
4087 07	1	1	644	1/10/120
4087 09	2	1	644	1/10/120
4087 10	3	1	644	1/10/120
4087 11	4	1	640	1/10/120
4087 12	6	1	536	1/10/120
4087 14	10	1	536	1/10/120
4087 16	16	1	536	1/10/120
4087 17	20	1	536	1/10/120
4087 18	25	1	536	1/10/120
4087 19	32	1	536	1/10/120
4087 20	40	1	■	1/10/120
4087 21	50	1	■	1/10/120
4087 22	63	1	■	1/10/120

Single pole + neutral 240V

4087 26	0.5	2	1674	1/5/60
4087 27	1	2	1674	1/5/60
4087 29	2	2	1674	1/5/60
4087 30	3	2	1674	1/5/60
4087 31	4	2	1674	1/5/60

Double pole 415V

4087 32	0.5	2	1754	1/40
4087 33	1	2	1754	1/40
4087 35	2	2	1754	1/40
4087 36	3	2	1754	1/40
4087 37	4	2	1754	1/40
4087 38	6	2	1326	1/40
4087 40	10	2	1326	1/40
4087 42	16	2	1326	1/40
4087 43	20	2	1326	1/40
4087 44	25	2	1326	1/40
4087 45	32	2	1326	1/40
4087 46	40	2	■	1/40
4087 47	50	2	■	1/40
4087 48	63	2	■	1/40



4087 46

* MRP - Maximum Retail Price Inclusive of all taxes including GST.
■ Price available on request.

D Curve



4087 52

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

Triple pole 415V

4087 52	0.5	3	2612	1/32
4087 53	1	3	2612	1/32
4087 55	2	3	2612	1/32
4087 56	3	3	2612	1/32
4087 57	4	3	2612	1/32
4087 58	6	3	2140	1/32
4087 60	10	3	2140	1/32
4087 62	16	3	2140	1/32
4087 63	20	3	2140	1/32
4087 64	25	3	2140	1/32
4087 65	32	3	2140	1/32
4087 66	40	3	■	1/32
4087 67	50	3	■	1/32
4087 68	63	3	■	1/32

Triple pole + neutral 415V

4087 72	0.5	4	3184	1/32
4087 73	1	4	3184	1/32
4087 75	2	4	3184	1/32
4087 76	3	4	3184	1/32
4087 77	4	4	3184	1/32

Four pole 415V

4087 78	0.5	4	3176	1/32
4087 79	1	4	3176	1/32
4087 81	2	4	3176	1/32
4087 82	3	4	3176	1/32
4087 83	4	4	3176	1/32
4087 84	6	4	2800	1/32
4087 86	10	4	2800	1/32
4087 88	16	4	2800	1/32
4087 89	20	4	2800	1/32
4087 90	25	4	2800	1/32
4087 91	32	4	2800	1/32
4087 92	40	4	■	1/32
4087 93	50	4	■	1/32
4087 94	63	4	■	1/32



4087 90

Circuit breakers AC applications 80 - 125A

10 kA as per IEC 60947-2
Integrated label holder
Sliding insulating shield
Color coded contact indication window
IP 20 protected terminals
50 sq mm terminals

Single pole 230V / 400V

4085 99	80	1.5	3458	1/5/160
4086 00	100	1.5	3784	1/5/161
4086 01	125	1.5	4106	1/5/162



4086 00

Bold Cat.Nos are products normally available with Legrand (India) Stockists.
Cat.Nos that are not bold - delivery within 4 - 8 weeks from the date of order.
Bold packing quantity is our mandatory packing. Orders to be placed by Legrand (India) Stockist in multiples of the same.

DX³ MCB

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

Double pole 230V / 400V*

4086 40	80	3	7664	1/5/60
4086 41	100	3	8168	1/5/60
4086 42	125	3	8894	1/5/60

Triple pole 400V*

4086 62	80	4.5	12316	1/9
4086 63	100	4.5	13118	1/9
4086 64	125	4.5	14418	1/9

Four pole 400V*

4087 03	80	6	15882	1/9
4087 04	100	6	16548	1/9
4087 05	125	6	18538	1/9

DX³ DC MCBs

Circuit breakers DC applications upto 63A

6 kA as per IEC 60947-2
Integrated label holder
Sliding bottom clamp
Improved air channels
Color coded On/Off indication on dolly
Biconnect lower terminals
IP 20 protected terminals
Sliding shutters

Single pole 250V

4087 98	0.5	1	952	1/10/120
4087 99	1	1	952	1/10/120
4088 01	2	1	952	1/10/120
4088 02	3	1	952	1/10/120
4088 03	4	1	952	1/10/120
4088 04	6	1	788	1/10/120
4088 06	10	1	788	1/10/120
4088 08	16	1	788	1/10/120
4088 09	20	1	788	1/10/120
4088 10	25	1	788	1/10/120
4088 11	32	1	796	1/10/120
4088 12	40	1	1052	1/10/120
4088 13	50	1	1052	1/10/120
4088 14	63	1	1052	1/10/120

Double pole 250V

4088 15	0.5	1	1986	1/5/60
4088 16	1	1	1986	1/5/60
4088 18	2	1	1986	1/5/60
4088 19	3	1	1986	1/5/60
4088 20	4	1	1986	1/5/60
4088 21	6	1	1842	1/5/60
4088 23	10	1	1842	1/5/60
4088 25	16	1	1842	1/5/60
4088 26	20	1	1842	1/5/60
4088 27	25	1	1842	1/5/60
4088 28	32	1	1842	1/5/60
4088 29	40	1	2172	1/5/60
4088 30	50	1	2172	1/5/60
4088 31	63	1	2172	1/5/60

* MRP - Maximum Retail Price Inclusive of all taxes including GST.
♦ For further details on product contact nearest Legrand Sales Office.

DX³ MCB

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

DX³ RDSO DC MCB

Single pole

4088 32	0.5	1	976	1/10/120
4088 33	1	1	976	1/10/120
4088 34	1.5	1	976	1/10/120
4088 35	1.6	1	976	1/10/120
4088 36	2.5	1	976	1/10/120
4088 37	3	1	714	1/10/120
4088 38	4	1	714	1/10/120
4088 39	5	1	868	1/10/120
4088 40	10	1	868	1/10/120
4088 41	15	1	868	1/10/120
4088 42	20	1	868	1/10/120
4088 43	25	1	868	1/10/120
4088 44	30	1	990	1/10/120
4088 45	35	1	990	1/10/120
4088 46	40	1	1102	1/10/120
4088 47	50	1	1102	1/10/120
4088 48	60	1	1102	1/10/120

DX³ isolators

Isolators for AC applications upto 125A

ISI marked as per IEC 60947-3
Integrated label holder
Ergonomic red color dolly
Sliding bottom clamp
Double break mechanism
Improved air channels
Color coded On/Off indication on dolly
Biconnect lower terminals
IP 20 protected terminals
Compatible with signal and control Auxiliaries
Sliding shutters

Double pole 240V

4065 00	32	2	678	1/5/60
4065 01	40	2	746	1/5/60
4065 02	63	2	986	1/5/60
4065 04	100	2	1354	1/5/60
4065 05	125	2	1540	1/5/60

Triple pole 415V

4065 09	32	3	1222	1/40
4065 10	40	3	1310	1/40
4065 11	63	3	1560	1/40
4065 13	100	3	1722	1/40
4065 14	125	3	1986	1/40

Four pole 415V

4065 18	32	4	1340	1/32
4065 19	40	4	1664	1/32
4065 20	63	4	1836	1/32
4065 22	100	4	2218	1/32
4065 23	125	4	2444	1/32

Bold Cat.Nos are products normally available with Legrand (India) Stockists.
Cat.Nos that are not bold - delivery within 4 - 8 weeks from the date of order.
Bold packing quantity is our mandatory packing. Orders to be placed by Legrand (India) Stockist in multiples of the same.

Isolators for AC applications upto 125A

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

DX³ RCCBs

RCCBs for AC applications upto 63A

ISI marked as per IS 12640-1

Integrated label holder

Ergonomic Grey color dolly

Sliding bottom clamp

Compatible with signal and control Auxiliaries

Color coded On/Off indication on dolly

Biconnect lower terminals

IP 20 protected terminals

35 sq mm terminals

Sliding shutters

Type - AC

Sensitive to residual alternating currents

Use : standard applications

Double pole 240V

30 mA

4118 51	25	2	4022	1/5/60
4118 52	40	2	4670	1/5/60
4118 53	63	2	5740	1/5/60

100 mA

4118 56	25	2	4430	1/5/60
4118 57	40	2	5116	1/5/60
4118 58	63	2	6092	1/5/60

300 mA

4118 61	25	2	4506	1/5/60
4118 62	40	2	5214	1/5/60
4118 63	63	2	6116	1/5/60

Four pole 415V

30 mA

4118 76	25	4	5514	1/32
4118 77	40	4	5652	1/32
4118 78	63	4	6288	1/32

100 mA

4118 81	25	4	5814	1/32
4118 82	40	4	5882	1/32
4118 83	63	4	6918	1/32

300 mA

4118 86	25	4	5988	1/32
4118 87	40	4	6076	1/32
4118 88	63	4	6942	1/32

Type- S

Delayed trip for discrimination with other residual current devices.

Use : for discrimination with a downstream device

Double pole 415V, A-S

300 mA

4118 66	25	2	7742	1/5/60
4118 67	40	2	8128	1/5/60
4118 68	63	2	8364	1/5/60

Four pole 415 V, A-S

300 mA

4118 91	25	4	8718	1/5/60
4118 92	40	4	8830	1/5/60
4118 93	63	4	9226	1/5/60



4118 57



4118 77



4118 83



4118 93

RCCBs for AC applications upto 63A

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

Type Hpi

Enhanced immunity to unwanted tripping in environments with disturbances. eg. diesels, computers, printers, etc.

• Detects faults with DC components eg. thyristors, trio etc.

Double pole 240V HPI

30 mA

4118 71	25	2	8466	1/5/60
4118 72	40	2	8888	1/5/60
4118 73	63	2	9146	1/5/60

Four pole 415V HPI

30 mA

4118 96	25	4	9590	1/32
4118 97	40	4	9892	1/32
4118 98	63	4	10148	1/32

DX³ RCBOs

RCBOs assembled for AC applications upto 63A

ISI marked as per IS 12640-2

Integrated label holder

Ergonomic design

Color coded On/Off indication on dolly

Compatible with signal and control Auxiliaries

Front face indication for earth leakage fault

IP 20 protected terminals

35 sq mm terminals

Sliding shutters

Type - AC

Sensitive to residual alternating currents

Use : standard applications

Double pole 240V AC Type

30 mA

4113 22	6	4	5010	1/32
4113 23	10	4	5010	1/32
4113 24	16	4	5066	1/32
4113 25	25	4	5066	1/32
4113 26	32	4	5288	1/32
4113 27	40	4	6072	1/32
4113 28	63	4	7398	1/32

100 mA

4113 29	6	4	6242	1/32
4113 30	10	4	6242	1/32
4113 31	16	4	6036	1/32
4113 32	25	4	6036	1/32
4113 33	32	4	6036	1/32
4113 34	40	4	6892	1/32
4113 35	63	4	7954	1/32

300 mA

4113 36	16	4	6272	1/32
4113 37	25	4	6272	1/32
4113 38	32	4	6272	1/32
4113 39	40	4	7072	1/32
4113 40	63	4	7968	1/32



4118 97



4113 24

* MRP - Maximum Retail Price Inclusive of all taxes including GST.

Bold Cat.Nos are products normally available with Legrand (India) Stockists. Cat.Nos that are not bold - delivery within 4 - 8 weeks from the date of order. Bold packing quantity is our mandatory packing. Orders to be placed by Legrand (India) Stockist in multiples of the same.

RCBOs assembled for AC applications upto 63A

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

Four pole 415V, AC type 30 mA

4113 65	16	7	6766	1/16
4113 66	25	7	6766	1/16
4113 67	32	7	6978	1/16
4113 68	40	7	7102	1/16
4113 69	63	7	8146	1/16

Four pole 415V, AC type 100 mA

4113 70	16	7	7626	1/16
4113 71	25	7	7626	1/16
4113 72	32	7	7700	1/16
4113 73	40	7	7844	1/16
4113 74	63	7	8632	1/16

Four pole 415V, AC type 300 mA

4113 75	16	7	7864	1/16
4113 76	25	7	7864	1/16
4113 77	32	7	8000	1/16
4113 78	40	7	8160	1/16
4113 79	63	7	8784	1/16



4113 79

RCBOs compact for AC applications upto 32A, 6kA

Conforms to IEC 60947

Integrated label holder

Ergonomic design

Color coded On/Off indication on dolly

Front face indication for earth leakage fault

IP 20 protected terminals

35 sq mm terminals

Sliding shutters

Type- AC

Sensitive to residual alternating currents

Use : standard applications

Double pole 240V, AC type 30 mA

4113 90	6	2	5956	1/32
4113 91	10	2	5956	1/32
4113 92	16	2	5956	1/32
4113 93	20	2	5956	1/32
4113 94	25	2	5956	1/32
4113 95	32	2	6250	1/32



4113 94

300 mA

4113 97	6	2	6244	1/32
4113 98	10	2	6244	1/32
4113 99	16	2	6244	1/32
4114 00	20	2	6244	1/32
4114 01	25	2	6244	1/32
4114 02	32	2	6554	1/32

* MRP - Maximum Retail Price Inclusive of all taxes including GST.

RCBOs compact for AC applications

Cat.Nos	Description	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	-------------	---------------------------	---------------	------

Four pole 415V, AC type 30 mA

4114 18	10	4	8138	1/16
4114 19	16	4	8138	1/16
4114 20	20	4	8138	1/16
4114 21	25	4	8138	1/16

Four pole 415V, AC type 300 mA

4114 23	10	4	9350	1/16
4114 24	16	4	9350	1/16
4114 25	20	4	9350	1/16
4114 26	25	4	9350	1/16

Type Hpi

Enhanced immunity to unwanted tripping in environments with disturbances. eg. diesels, computers, printers, etc.

• Detects faults with DC components eg. thyristors, trio etc.

Double pole 240V, HPI type 30 mA

4114 15	25	2	11352	1/32
4114 16	32	2	12002	1/32

Type A

Sensitive to residual alternating currents and residual currents with a DC component.

Use : special applications

- if it is possible that the fault currents are not purely sinusoidal (rectifier bridge, etc.)

Four pole 415V, A type 30 mA

4114 28	10	4	9178	1/16
4114 29	16	4	9178	1/16
4114 30	20	4	9178	1/16
4114 31	25	4	9178	1/16

Four pole 415V, A type 300 mA

4114 33	10	4	10346	1/16
4114 34	16	4	10346	1/16
4114 35	20	4	10346	1/16
4114 36	25	4	10346	1/16

DX³ RCD add on module

For 125A

Conform to IEC 61009-1

AC type : detect AC components faults

Hpi type : detect faults with AC and DC components, increased

Immunity to false tripping

For mounting on the right-hand side of 1.5 module per pole DX³ MCBs

Easy & fast association mechanism

Terminal cover for locking

70 sq mm terminals

Bold Cat.Nos are products normally available with Legrand (India) Stockists. Cat.Nos that are not bold - delivery within 4 - 8 weeks from the date of order. Bold packing quantity is our mandatory packing. Orders to be placed by Legrand (India) Stockist in multiples of the same.

RCBOs compact for AC applications



4105 68

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

Double pole 240V, AC type

30 mA

4105 68	125 A	4	18504	1
---------	-------	---	-------	---

100 mA

4105 69	125 A	4	20866	1
---------	-------	---	-------	---

300 mA

4105 71	125 A	4	20866	1
---------	-------	---	-------	---

Four pole 415V, AC type

30 mA

4106 25	125 A	4	28594	1
---------	-------	---	-------	---

100 mA

4106 26	125 A	4	31952	1
---------	-------	---	-------	---

300 mA

4106 29	125 A	4	31952	1
---------	-------	---	-------	---

Double pole 240V, HPI type

30 mA

4105 78	125 A	6	23114	1
---------	-------	---	-------	---

100 mA

4105 79	125 A	6	25836	1
---------	-------	---	-------	---

300 mA

4105 82	125 A	6	25836	1
---------	-------	---	-------	---

Four pole 415V, HPI type

30 mA

4106 38	125 A	6	39622	1
---------	-------	---	-------	---

100 mA

4106 39	125 A	6	41834	1
---------	-------	---	-------	---

300 mA

4106 42	125 A	6	41834	1
---------	-------	---	-------	---

Auxiliaries common for MCBs, isolators, RCCBs & RCBOs

Easy & fast fixation on site

On site clip on mounting

Clip on fitting on left side

Signalling auxiliaries

4062 50	Auxiliary changeover switch 6 A	0.5	1296	1
4062 52	Fault signalling changeover switch 6 A	0.5	1510	1
4062 64	Changeover + fault signalling switch	1	2392	1



4062 50



4062 52

DX³ auxiliaries

Cat.Nos	Description	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	-------------	---------------------------	---------------	------

Control auxiliaries

4062 76	Shunt release 12 /48 V AC/ DC	1	3328	1
4062 78	Shunt release 110/415 V V AC	1	3328	1
4062 80	Undervoltage release 24/48 V AC/DC	1	2834	1
4062 82	Undervoltage release 230 V AC	1	2834	1



4062 78



4062 82

Control auxiliaries

4062 86	Pop over voltage release	1	3612	1
4062 90	Motor control 24/48 V AC/ DC	1	13022	1
4062 91	Motor control 110/415 V AC	1	13022	1
4062 93	Motor control 24/48 V AC/ DC	2	24516	1
4062 95	Motor control 110/415 V AC	2	23156	1
4062 88	Automatic resetter	2	17292	1
4062 89	Automatic resetter with autotest	2	21642	1

Rotary handle

4063 19	Black rotary handle	-	2704	10
4063 20	Yellow/red rotary handle	-	2926	10

Support for padlock

4063 03	Support for padlock till 63 A	-	626	10
---------	-------------------------------	---	-----	----

Sealable screw cover

4063 04	Devices upto 63 A	-	620	10
4063 06	For 80-125 A devices	-	1082	10

1/2 module spacing unit

4063 07	1/2 module spacing unit	0.5	228	10
---------	-------------------------	-----	-----	----

5 mm padlock

4063 13	5 mm Padlock	0.5	530	10
---------	--------------	-----	-----	----

* MRP - Maximum Retail Price Inclusive of all taxes including GST.

Bold Cat.Nos are products normally available with Legrand (India) Stockists. Cat.Nos that are not bold - delivery within 4 - 8 weeks from the date of order. Bold packing quantity is our mandatory packing. Orders to be placed by Legrand (India) Stockist in multiples of the same.